



HAMMER

Product Overview

Our HAMMER gypsum is a gypsum mortar that is ready for direct use on bricks without lining whilst allowing for a soft, white surface with a thickness of up to 8cm per layer. It can also be immediately painted after drying. The HAMMER gypsum is available in a powdered form and is mixed with water to form a paste that can be directly applied to wall and ceiling surfaces at site.



HAMMER

25 kg



Packaging Available

6 Months



Shelf Life



Directions & Recommendations:

- Clean the surface from any dust by spraying it down with water.
- Clean water is placed in the mixing bowl by 50% of the weight of the used HAMMER mortar.
- Add the HAMMER mortar gradually to the water and leave to soak for 2 minutes.
- Mix well until completely homogenous to access the appropriate strength.



Advantages:

- Great workability and cost-effectiveness.
- No shrinkage or cracking.
- 50% lighter weight than traditional cement alternatives.
- Resistant to moisture, water and rain.
- Highly resistant to mould and mildew.
- Excellent temperature and sound insulating properties.
- Excellent fire resistance properties.
- Sustainable.

Technical Specifications:

Color	White
Density (kg/L)	0,8 ± 0,02
Setting Time	45 min
Water to Powder Ratio	2:1
Average Consumption	60 to 65 m2 (2cm layer thickness) per ton.

Contact Us

Phone:

+20 122 213 4010
+2 02 333 75 204
+2 02 333 75 206
+2 02 333 75 121

Fax: 0020233375181

E-mail : info@alalamia.co

Sales Inquiries : sales@alalamia.co

Careers: Please send your CV to hr@alalamia.co

Website: www.alalamia.co